

Kanaldielen, kaltgewalzt

Profil	Profil- breite	Wand- höhe	Rücken- dicke	Steg- dicke
	b	h	t	s
	mm	mm	mm	mm
HKD 400*	400	50,0	5,0	5,0
HKD 400/6*	400	50,0	6,0	6,0
HKD 700/8*	650	92,0	8,0	8,0
HKD 800*	800	100,0	8,0	8,0
KD II*	330	35,0	5,5	5,5
KD III*	375	38,0	5,5	5,5
KD III s*	375	40,0	6,5	6,5
KD 4 L	400	49,0	5,8	5,8
KD 6-6	600	78,0	6,0	6,0
KD 6-8	600	80,0	8,0	8,0
KD 750-8	750	92,0	8,0	8,0
KD 750-10	750	92,0	10,0	10,0
RC 8600	742	92,0	6,0	6,0
RC 8700	742	93,0	7,0	7,0
RC 8800	742	94,0	8,0	8,0

* Profile werden nicht mehr hergestellt

Verschiedene Hersteller

Eigenlast		Widerstands- moment (elast.) Wy	
kg/m Einzel- bohle	kg/m ² Wand (ca.)	cm ³ /m Wand	
18,4	46,0	85	
22,1	55,3	102	
53,0	81,5	287	
59,0	73,8	273	
17,0	51,5	55	
20,3	54,1	70	
23,3	62,1	80	
21,3	53,3	99	
37,5	62,5	186	
50,0	83,3	242	
55,3	73,7	260	
66,9	89,2	325	
40,9	55,1	194	
47,6	64,2	224	
54,2	73,1	254	